

No.	Packer	inch	Quick-Lock Mini
1.	VP 100-150 VFW 	4"	0100-140 B2
		5"	0125-140 B2
		6"	0150-140 B2
2.	VP 100-125 for bends 	4"	0100-090 B2
		5"	0125-090 B2
3.	VP 150 for bends 	6"	0150-090 B2
4.	VP-L 100-125 Mini 	4"	LEM 0100-140
		5"	LEM 0125-140
5.	VP-L 150 Mini 	6"	LEM 0150-140
6.	Connection for hydraulic-hose for <b>VP 100-125 for bends</b> und <b>VP 150 for bends</b> to use with Slide/ Push rods and Push Camera Systems. <u>Attention: hexagonal pin</u>		

With our new Quick-Lock System Mini, we will be able to open up an even broader range of applications for clients and users.

The Quick-Lock Mini works completely by mechanical means. Based on the compression principle and the proven materials V4A and EPDM. For the installation in standard pipe systems, downpipes and district heating piping, use our installation packer with adjustable chassis (see picture 1.) in connection with a corresponding camera.

Our Quick-Lock Mini with a length of 90 mm was developed for pipes with bends up to 45°. To move these sleeves, use our specially designed quick-lock packer (picture 2. and 3.).

For liner end connection, the Quick-Lock Mini System is available in nominal sizes DN 100 to DN 150 with length 140mm (picture 4. and 5.).